

TEDRA II

Thermo Couple Enhanced Disc Brake Radio Access

Product Information V2.0 2019/06/11



System Features:

- wireless communication in worldwide available 2.4 GHz frequency band:
2.4000 - 2.4835 GHz
- 16 radio channels with 5 MHz spacing (not overlapping)
- 4 channels thermocouple type K per transmitter
(other types optional available)
- 16 channel receiver
- CAN bus interface (CAN ID adjustable)
- USB interface (USB 1.1 / 2.0)
- automatic interference detection
- easy installation
- multi LED indication
- robust design

Innovation by Electronics



Sensor Electronics
System Solutions
Telemetry
Hardware
Software

**Instrumentation
Devices**

senTec Elektronik GmbH

Robert-Bosch-Ring 2
D-98693 Ilmenau

Tel.: +49 (0)3677 / 689 37 - 0
Fax: +49 (0)3677 / 689 37 29
Info@senTec-Elektronik.de

**sen
Tec**
ELEKTRONIK

Instrumentation Devices Srl

Via Acquanera 29 - 22100 COMO (Italy)
ph +39 031 525 391- fax +39 031 507 984

info@instrumentation.it - www.instrumentation.it

TEDRA II

Transmitter Features:

- battery lifetime up to 4 weeks
- automatic connection
- no interference with multiple system in parallel
- small batteries ½ AA with 3.6V (e.g. Li-Ion)



Receiver Features:

- automotive onboard voltage 9V...16V
- USB port (type B)
- CAN bus interface SUB-D
- standard measurement interval 1s (free configurable up to 0.1s)



Systems Standard Accessory:

- antenna
- power connector (12V DC banana plug and car connector)

Systems Optional Accessory:

- mounting disks
- suitcase
- clamping bolts

© senTec Elektronik GmbH. All Rights reserved.

Innovation by Electronics



Sensor Electronics
System Solutions
Telemetering
Hardware
Software

senTec Elektronik GmbH

Robert-Bosch-Ring 2
D-98693 Ilmenau

Tel.: +49 (0)3677 / 689 37 - 0
Fax: +49 (0)3677 / 689 37 29
Info@senTec-Elektronik.de

**sen
Tec**
ELEKTRONIK

**Instrumentation
Devices**

Instrumentation Devices Srl

Via Acquanera 29 - 22100 COMO (Italy)

ph +39 031 525 391- fax +39 031 507 984

info@instrumentation.it - www.instrumentation.it